Severe Service



SPECIFICATIONS

ACCURACY $\pm 2.5\%$ of range across full scale **CASE SIZES** 40 or 50 mm diameter CASE MATERIAL 304 Stainless Steel CASE STYLE CB – Center Back mount TUBE & SOCKET **Copper Alloy tube** with nickel plated brass socket MOVEMENT Brass CONNECTION 1% NPT & 1/4 NPT RANGES 15 to 160 psi **DIAL STANDARD** Triple scale psi/BAR/kPa **DIAL COLOR** Black markings on white POINTER Aluminum, black painted WINDOW Acrylic FILL MEDIUM **Glycerine Standard** RESTRICTOR Standard, all ranges **VENT PLUG** Filler/pressure relief plug **TEMPERATURE LIMITS** -4 to 140° F (filled) WEIGHT 40mm 0.5 lb. 50mm 0.5 lb.

40MM & 50MM SEVERE SERVICE GAUGE

- Copper Alloy Internals
- Glycerine Filled
- Center Back Mount Only

Marsh Instruments Liquid-Filled Gauges are designed to perform in rugged and harsh environmental conditions especially where pulsation and vibration is a problem. Liquid Filled Gauges offer a significant cushioning and dampening effect, reducing pointer flutter and internal gauge damage. Liquid Filled Gauges feature a ventable top fill plug and can be mounted on a horizontal or vertical plane. The hermetically sealed construction reduces the chance of leaks and makes field filling an easy option.


Typical applications include refineries, chemical, oil & gas, marine and OEM processes.

STANDARD RANGES & PART NUMBERS

ТҮРЕ	40MM & 50MM GAUGES	
Size	40mm	50mm
Case Material	304 Stainless Steel	304 Stainless Steel
Internals	Copper Alloy	Copper Alloy
Mounting / Case Style	CB	CB
Connection	½ NPT	1/4 NPT
Scale Standard	psi/BAR/kPa	psi/BAR/kPa
O to 15 psi	M4040P	M5040P
O to 30 psi	M4042P	M5042P
O to 60 psi	M4046P	M5046P
0 to 100 psi	M4048P	M5048P
0 to 160 psi	M4052P	M5052P

40MM AND 50MM GAUGE OPTIONS

OPTION	ТҮРЕ	SUFFIX	AVAILABLE ON MODELS	
Custom Dials	Custom face	М	See Marsh Price List for minimums	
Other Ranges			Consult factory for availability	
Fill Medium	Silicone (SL)	I	Consult factory	



A-Size	В	С	E
40mm Dia.	27.00mm	11.5mm	13.00mm
	1.06″	0.45″	0.51″
50mm Dia.	30.00mm	11.5mm	10.00mm
	1.18″	0.45″	0.39″

ALL DIMENSIONS ARE NOMINAL

ountain ontrols



tain ontrols Mail: mountaincontrolsinc@gmail.com Web: www.mountaincontrols.com Phone: 801-487-8795 Salt Lake City, UT 84109

Portable Ventilators Fans & Blowers Welding Fume Exhausters **Mist Coolers & Duct**

Ball Valves and Actuators Spring Return Electric Actuators Resilient Seated Butterfly Valves High Performance Butterfly Valves

Pressure Gauges Thermometers **Needle Valves and Diaphragm Seals**

Precision Air Regulators Air, Gas, Steam & Water Regulators Vacuum and Backpressure Regulators I/P and E/P Transducers

Temperature Indicators Temperature Switches **Capillary Bulb Type**

Process Controllers Multi-Loop **Process Indicators with Switches**

Control Valves – Globe Type Temperature Regulators Self Contained **Temperature Controllers**

Electric Actuators Modulating Controllers Spring Return – SURE Mounting to your valves.

Ball Valves - 3-piece **Pneumatic Actuators Electric Actuators Specialty Valves**

Solenoid Valves Water - Air - Hot Water - Steam **Pilot Valves**

We stock electric actuators and can provide the mounting and testing to the valve of your choice

Fax: 801-487-8798